



V Series

SD9367-EHL

2MP Outdoor AI PTZ Camera



Technical Specifications

System Information

CPU	Multimedia SoC (System-on-Chip)
Flash	8 GB
RAM	2 GB

Camera Specifications

Image Sensor	1/2.8" Progressive CMOS
Max. Resolution	1920x1080 (2MP)
Lens Type	40x Optical Zoom, Auto Focus
Focal Length	f = 4.25 ~ 170 mm (40x zoom)
Aperture	F1.6 ~ F4.95
Iris Type	DC-iris
Field of View	65.7° ~ 1.9° (Horizontal) 39.4° ~ 1.1° (Vertical) 73.0° ~ 2.1° (Diagonal)
Shutter Time	1 sec. to 1/100,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Minimum Illumination	0.05 lux @ F1.6 (Color)(30IRE) <0.005 lux @ F1.6 (B/W)(30IRE)
Pan Speed	0.05° ~ 450°/sec
Pan Range	360° endless
Tilt Speed	0.05° ~ 450° /sec
Tilt Range	-20° ~ +90° (Effective tilt coverage 220° via auto flip)
Preset Location	256 preset locations / 128 presets per tour

Pan/Tilt/Zoom Functionalities	8x digital zoom Auto Pan mode Auto Patrol mode Mechanical Auto flip
Storage	Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS)
Built-in Installation Aids	Remote focus, Remote zoom

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 1920x1080 (WDR on) 60 fps @ 1920x1080 (WDR off)
Maximum Streams	3 video streams (Up to 8 configurable profiles)
S/N Ratio	60 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constrained bit rate control, Smart Stream III
Image Settings	General settings video title and time stamp overlay, video orientation (flip, mirror), day/night settings Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, HLM, 3DNR, EIS, scene mode (auto, deblur) Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR Focus Privacy mask Pixel calculator Scheduled profile settings

Audio	
Audio Capability	Two-way Audio (full duplex)
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	External line input External line output

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Account block, Audit log, Session timeout, Configurable password strength protection, Digest authentication, CSRF protection, HTTPS, IEEE 802.1x, Secure boot, Signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event, quarantine event), DoS Protection, User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP/SFTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTCIP, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2/1.3, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T, M supported, specification available at www.onvif.org

AI Analytics

Compute Capability	SoC with built-in hardware deep learning accelerator
Vision Object Analytics	Object Detection: People Vehicle (4-wheeled, 2-wheeled) Human / Vehicle Bestshot Attribute Extraction: People (gender, clothing color, bag, hat) Path Extraction Vehicle (bike, bus, car, motorcycle, truck, color) Human face Bestshot Re-Search Extraction
Applications	Deep Learning VCA (Smart Tracking Advanced) Smart VCA - Group 1 Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, Face detection) Smart VCA - Group 2 Unattended object detection, Missing object detection
Application available with license	Smart VCA - Group 3 Parking Violation Detection, Restricted Zone Detection *Support for more analytic applications and free trial, please visit VIVOTEK website.

Solution Integration	
VADP Package	Trend Micro IoT Security (3-year free trial), Event action through HTTP/HTTPS
Video Motion Detection	Motion Detection (Five-window video motion detection)

Alarm and Event	
Event Trigger	Motion detection, Camera tampering detection, Audio detection*, Digital input*, Manual trigger, Periodical trigger, System boot, Recording notification, SD card life expectancy, Smart tracking advanced trigger, Preset reached, Cybersecurity events (brute force attack event, cyberattack event, quarantine event) * Requires AO-008 cable
Event Action	Event notification via email, HTTP, FTP/SFTP, NAS server, SD card, digital output*, audio clip*, camera link, push notification File upload via email, HTTP, FTP/SFTP, NAS server, SD card *Requires AO-008 cable

General	
Connectors	RJ-45 cable connector for 10/100 Mbps Network/PoE connection Audio line input * Audio line output * DC 48V power input AC 24V power input Digital input *2 * Digital output *1 * RS-485 *1 * * Requires AO-008 cable
LED Indicator	System power and status indicator
Power Input	AC 24V, DC48V, IEEE 802.3at PoE Class 4 (Simultaneous Power Redundancy Supported)
Power Consumption	PoE Max: 22.5W/25.5W (Heater & Fan off/on) DC 48V Max: 22.5W/25.5W (Heater & Fan off/on) AC 24V Max: 22.5W/25.5W (Heater & Fan off/on)
Dimensions	174 (D) x 276 (H) mm
Weight	4.5 kg

Certifications	EMC CE (EN 55032 Class A, EN 55035, EN 50121-4), UKCA (BS EN 55032:2015+A11:2020, BS EN 55035:2017), FCC (FCC Part 15 Subpart B Class A), IC (ICES-003:2020 Issue 7, Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A) Safety UKCA (BS EN 62368-1:2014+A11:2017), UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 60950-22, IEC/EN 62471) Environment IK10 (IEC 62262), IP66 (IEC 60529), NEMA (NEMA 250 Type 4X) IA BIS (IS 13252), BSMI (EMC: CNS 15936, Safety: CNS 15598-1)
Operating Temperature	Starting Temperature: -40°C ~ 55°C (-40°F ~ 131°F) Working Temperature: -40°C ~ 55°C (-40°F ~ 131°F)
Humidity	98% RH (non-condensing)
Warranty	60 months

System Requirements

Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above
Other Players	VLC: 1.1.11 or above

Included Accessories

Packing Contents	T25 L-wrench, Quick installation guide, Waterproof round cap, Ground wire, Terminal blocks (for DI/DO audio, AC/DC/GND wires, RS485)
------------------	--

DORI (EN 62676-4 Standard)

Detection (25PPM/ 8PPF)	Wide: 61.1 m (200.5 ft) Tele: 2370 m (7775.6 ft)
Observation (63PPM/ 19PPF)	Wide: 24.4 m (80.1 ft) Tele: 854.15 m (2802.3 ft)
Recognition (125PPM/ 38PPF)	Wide: 12.2 m (40.0 ft) Tele: 414.2 m (1358.9 ft)
Identification (250PPM/ 76PPF)	Wide: 6.1 m (20.0 ft) Tele: 208.3 m (683.4 ft)